



Jig Saw

4350FCT **Top Handle Type**
4351FCT **Body Handle Type**

Satisfy Professional's Needs



Bayonet shank
Jig Saw Blade



**HIGH QUALITY &
RELIABILITY**
by Superior Maneuverability



Toolless Blade Change

Enables extremely
quick blade changes.

Low Noise
Low Vibration

Electronic
Control

LED
Job Light


Capacity in Wood
135mm

Powerful Motor
720W

Makita

Low Noise & Low Vibration

employs lightweight Rod and balance plate mechanism* to reduce vibration dramatically. Reducing vibration makes operator feel more comfortable when cutting various workpieces.



*balance plate mechanism: Counterbalance mechanism to reduce vibration by moving Plate in the opposite direction of Rod

Electronic Control



• Variable Speed Control by Dial ensures optimum cutting speed per job.

- Constant Speed Control keeps minimizing the speed loss under loaded conditions.
- Soft Start suppresses the shock when starting.

LED Job Light

Ergonomically designed rubberized grip provides more control and comfort.



3 Orbital settings + Straight cutting

Optimum cutting action can be selected by simply turning the change lever.

Dust Nozzle

(Standard Equipment: European countries only)



Can be connected to vacuum with Hose Complete 28-5.

Cover Plate
Protects workpiece from scratches

Bevel cutting

Aluminum base can be tilted up to 45-degrees to the left or right.

Rigid Aluminum Base

Blower function keeps the cut line clean.



Comparison of Cutting Efficiency

Note: 1. The test results depend to a great extent on the hardness of materials, etc.
2. The numbers in the charts below are relative values when the capacities of 4340FCT are indexed at 100.

Test conditions:

Test material: 48mm thick MDF

Orbital mode: 3 Blade: B-10

Work speed




Test conditions:

Test material: 3.2mm thick SPCC

Orbital mode: 0 Blade: B-22

Work speed



Accessories

Guide Rail

1.4m: Part No. 194368-5

3.0m: Part No. 194367-7



Guide Rule Set

Part No. 193516-3



Cover Plate

Part No. 417852-6



Dust Nozzle

Part No. 417853-4



Guide Rail Adapter Set

Part No. 193517-1



Anti-Splintering Device

(For cleaner cuts)

Part No. 192557-6



Hose Complete 28-5

Part No. A-34229



Jig Saw

Double Insulation

Orbital Cutting

Bayonet Shank Jig Saw Blade

Dust Collecting

Electronic Speed Control

Variable Speed

Soft Start

Built-in Job Light

Carrying Case



4350FCT

4351FCT

	4350FCT	4351FCT
Continuous rating Input	720W	720W
Capacity		
In wood at 90 degrees	: 135mm	: 135mm
In steel at 90 degrees	: 10mm	: 10mm
Length of stroke	26mm	26mm
Strokes per minute (spm)	800 - 2,800	800 - 2,800
Dimensions (L x W x H)	236 x 73 x 207mm	271 x 73 x 187mm
Net weight	2.5kg	2.5kg
Power supply cord	2.5m	2.5m

* when cutting with optional blade No. B-16L

Standard Equipment : Jig Saw Blade Set, Hex Wrench, Cover Plate, Anti-Splintering Device