

Cordless Combination Hammer DHR280 / DHR281 / DHR282 AWS DHR283 AWS 28 mm (1-1/8")









DHR280 DHR282 AWS















Excellent Power and Low Vibration




Max Bit length: 260mm



Filter cleaning mechanism

by turning the dial, the dust falls off from the filter







Brushless Motor

Work Speed

About 40 Predecessor Model

Work Volume

■ Pred ecessor Model



Concrete with compressive strength of 40N/mm² Diameter: Ø12.5mm(1/2"), depth of 60mm(2-3/8")



AVT Anti Vibration Technology

Less Vibration

Vibration level

[Chiselling] 8.0m/s²/ [Drilling (into metal)] 2.5m/s²

[Hammer drilling] (into concrete) m/s²









Accessories

Wireless Unit

198901-5, 198900-7(EU), 199393-1(Asia)









AFT Active Feedback sensing Technology

DHR282, DHR283 only



Features and benefits

	DHR280	DHR281	DHR282	DHR283
Quick change drill chuck		V		V
AFT			V	V
AWS			V	V
AVT	V	V	V	V
Dust extraction system set	DX08	DX09	DX08	DX09



Depth gauge

Twin LED job light





can be adjusted for desired drilling depth simply by pushing single push button





HILL

HEPA

Tnakita.

Dust collection inlet

can be adjusted according to bit length simply by pushing single push button

Large dust box cover

can be opened simply by pushing single push button for easy dust cleaning.




Photo: DHR280 & DX08

Transparent dust case

for easy checking of collected dust amount



Filter cleaning mechanism

Accessories

Dust extraction system set

DX08 DHR280, DHR282

DX09 for DHR281, **DHR283**



Dust case

Part No. 199555-1



HEPA Filter

High Efficiency Particulate Air filter is widely regarded as ultimate filter that traps all sizes of particles with an efficiency rating of 99.75%.

Part No. 199557-7





DHR280, DHR282 Part No. 195173-3

DHR281, DHR283 Part No. 195179-1



Cordless Combination Hammer DHR280 / DHR281 / DHR282 / DHR283





Reversing



SDS-PLUS Shank



Constant Speed





Built-in Job Light



Impact Energy . Capacity

Blows Per Minute (BPM) No Load Speed (RPM) Chuck capacity Vibration Level

Sound Pressure Level Sound Power Level Dimensions (L x W x H) Net weight

DHR280 / DHR282

EPTA-Procedure 05/2009: 2.8 J Concrete / Steel / Wood / Core Bit / Diamond Core Bit (Dry Type) 28 / 13 / 32 / 54 / 65 mm (1-1/8" / 1/2" / 1-1/4" / 2-1/8" / 2-9/16") 0 - 5,000 0 - 980

1.5 - 13 mm (1/16 - 1/2") Hammer Drilling into Concrete: 9.0 m/s² Drilling Into Metal: 2.5 m/s² 93 dB(A)

104 dB(A) 373x134x232 mm (14-3/4"x5-1/4"x9-1/8") DHR280: 3.9 - 4.9 kg (8.6 - 10.8 lbs.) DHR282: 3.9 - 5.0 kg (8.6 - 11.0 lbs.)

DHR281 / DHR283

EPTA-Procedure 05/2009: 2.8 J Concrete / Steel / Wood / Core Bit / Diamond Core Bit (Dry Type). 28 / 13 / 32 / 54 / 65 mm (1-1/8" / 1/2" / 1-1/4" / 2-1/8" / 2-9/16")

0 - 5,000 0 - 980

1.5 - 13 mm (1/16 - 1/2") Hammer Drilling into Concrete: 9.5 m/s² Drilling Into Metal: 2.5 m/s²

92 dB(A) 103 dB(A)

404x134x232 mm (15-7/8"x5-1/4"x9-1/8") DHR281: 4.0 - 5.1 kg (8.8 - 11.2 lbs.) DHR283 : 4.1 - 5.1 kg (9.0 - 11.2 lbs.)

Standard Equipment:

DHR280, DHR282: Side Grip, Depth Gauge, Battery, Charger, Dust Cup (country-specific), Cleaning cloth (country-specific), Bit Grease (country-specific)

DHR281, DHR283: Quick Change Drill Chuck, Side Grip, Depth Gauge, Battery, Charger, Dust Cup (country-specific), Cleaning cloth (country-specific), Bit Grease (country-specific)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.



Makita Corporation