



Rotary Hammer
HR4002 40mm

Satisfy Professional's Needs



**TOP EFFICIENCY
AND SPEED**



2 Mode Change Lever

Hammering with Rotation

Hammering

Chisel locking at 12 different positions



Slide Chuck



Push-in and Go


Slide-back and Pull



Compact 458mm


No Hammering when Idling

No Hammering while idling because air in the cylinder is not compressed unless tool is pressed against ground. This function ensures machine's long life.



Torque Limiter

When drill bit hits against reinforcements, Torque Limiter operates to stop the rotation of drill bit, ensuring safety in your work.



Rubberized Grip

Provides more comfort and control while minimizing hand fatigue and pain.



Aluminum Housing

Provides high quality and toughness.

Auto Cut-Out Carbon Brush

When Carbon Brush wears out, it will automatically stop the motor. It protects commutator and indicates time for maintenance.

Rotary Hammer

- Double Insulation
- Torque Limiter
- Carrying Case



HR4002 40mm

350

Continuous rating Input	1,050W
Max. bit dia.	40mm
Max. core bit dia.	105mm
Blows per minute	2,500bpm
No load speed	680r/min
Dimensions (L x W x H)	458mm x 114mm x 256mm
Net weight	6.2kg
Power supply cord	5.0m