

# Makita®



## OUTDOOR POWER EQUIPMENT



DCU180Z	11
DJR183Z	6
DLM380DZ	8
DLM461Z	8
DUB183Z	8
DUB361Z	9
DUB362Z	9
DUC122Z	4
DUC254Z	5
DUC256Z	4
DUC302Z	4
DUC400Z	4
DUH523Z	69
DUH651Z	9
DUH602Z	10

DUM60Z	6
DUP362Z	7
DUR181Z	7
DUR187LZ	7
DUR364LZ	7
DUR365UZ	7
DUX60Z	11
EA3502S	6
EA4301F45C	6
RBC411U	8
RBC413U	8
UC4041A	4
UC4051A	6
UH6570	9

# High Performance with Brushless DC Motor

## Brushless DC motor


:: Maintenance-free due to no brush  
:: Energy production is more efficient than brushed DC motor because of no friction loss caused by brushes, enabling to lower amperage for reduced heat production and increased work amount on a single full battery charge.

## More work amount on a single full battery charge

:: Thanks to the very efficient energy production of BLDC motor, work amount on a single full battery charge is increased.  
:: Life time work amount of a battery is increased, reducing the battery cost.

## Durable against continuous

:: Use of BLDC motor lowers heat production; the temperature rise at housing surface can be recessed well even in hard industrial applications requiring continuous long operation.







# Li-Ion Battery & Charger Time Reference, Compatibility Chart

3

## LXT

18V Lithium-ion		DC18RC Fast Charger		DC18SE Automotive Charger		DC18RD Two Port Multi Fast Charger
6.0 Ah	 BL1860B (197422-4) *BL1860B with Battery Fuel Gauge*	WITH DC18RC <b>55 min.</b> Fast Charging		WITH DC18SE <b>130 min.</b>		
5.0 Ah	 BL1850B (197280-8) *BL1850B with Battery Fuel Gauge*	<b>45 min.</b> Fast Charging		<b>110 min.</b>		
3.0 Ah	 BL1830B (197599-5) *BL1830B with Battery Fuel Gauge*	<b>22 min.</b> Fast Charging		<b>60 min.</b>		

No discharging  
required



Shock Absorbing  
Heavy Duty Pack



Longtime Storage  
Low Self Discharge



# 710%

## Extreme Stamina

The figure is a relative value when the amount of Ni-Cd 1.9Ah is indexed at 100.

## Life time work volume (5.0Ah)

The built-in CPU in battery records the battery usage history and transmits it to the charger.



Digital  
Communication

### Built-in CPU

The CPU built in the charger analyzes its condition; high temperature, re-charge after full charged, over-discharging. The battery lasts long life because it can be charged at the best method and time.



## 40%Lighter



MAKITA  
18V  
Ni-MH 2.8Ah

MAKITA  
18V Li-ion 5.0Ah



### Firm Holding

Multi-contact terminals reduce electrical resistance and increase connection stability withstanding against vibration, and ultimately ensures Stable current supply to the tool.



**DUC122Z****18V LXT Li-Ion Cordless 115mm, Automatic Oiling, Chain Brake, Brake****Cordless Chain Saw**

Low noise level and zero emissions for operator comfort.



Guide Bar Length	115 mm (4-1/2")
Chain Pitch	1/4"
Chain Gauge	1.3 mm (0.05")
Chain Speed	5.0 m/s (300 m/min) (980 FPM)
Chain Oil Tank Volume	80 mL (2.7 US oz)
Sound Pressure Level	84.6 dB(A)
Sound Power Level	92.7 dB(A)
Vibration Level	Cutting Wood: 4.3 m/s <sup>2</sup>
Dimensions (L x W x H)	422x195x215 mm (16-5/8"x7-5/8"x8-1/2")
Net weight	2.6 kg (5.7 lbs.)

**DUC256Z****18V X 2 (36V) LXT Li-Ion Cordless 250mm, Variable Speed, Brake, Soft Start****Cordless Chain Saw**

Guide Bar Length	250 mm (10")
Chain Pitch	1/4A
Chain Gauge	1.3 mm
Chain Speed	20 m/s
Chain Oil Tank Volume	200mL (6.8 US oz)
Sound Power Level	102dB(A)
Vibration Level	2.0m/s <sup>2</sup>
Dimensions (L x W x H)	270x205x232mm
Net weight	4.7 kg

**DUC302Z****18V X 2 (36V) LXT Li-Ion Cordless 300mm, Automatic Oiling, Chain Brake, Brake****Cordless Chain Saw**

Battery capacity warning lamp.



Guide Bar Length	300 mm (12")
Chain Pitch	3/8"
Chain Gauge	1.1 mm (0.043")
Chain Speed	8.3 m/s (500 m/min) (1,650 FPM)
Chain Oil Tank Volume	85 mL (2.9 US oz)
Sound Pressure Level	84.4 dB(A)
Sound Power Level	95.4 dB(A)
Vibration Level	Cutting Wood: 6.3 m/s <sup>2</sup>
Dimensions (L x W x H)	600x234x198 mm (23-5/8"x9-1/4"x7-3/4")
Net weight	4.7 kg

**DUC400Z****18V X2 (36V) LXT BL Brushless Cordless Chain Saw, Var. Speed, Brake, Chain Brake, Constant Speed, Automatic Oiling****Cordless Chain Saw**

Battery capacity warning lamp.



Guide Bar Length	400 mm (16")
Chain Pitch	370 mm (14-1/2")
Chain Gauge	3/8"
Chain Speed	1.1 / 1.3 mm (0.043" / 0.050")
Chain Oil Tank Volume	200 mL
Sound Pressure Level	87.7 dB(A)
Sound Power Level	100.4 dB(A)
Vibration Level	Cutting Wood: 5.3 m/s <sup>2</sup>
Dimensions (L x W x H)	800x215x235 mm (31-1/2"x8-1/2"x9-1/4")
Net weight	4.9- 5.4 kg (10.7 - 11.8 lbs.)

**UC4041A****220V, 400mm, Automatic Oiling, Chain Brake, Brake, 1800W****Electric Chain Saw**

High transmission durability.



Continuous rating input	1,800W
Chain speed per minute	870 m (2,900 ft)
Guide Bar Length	400 mm (16")
Saw chain	Pitch : 3/8"
Gauge: 1.1 mm (0.043") / 1.3 mm (0.050")	
Sound Pressure Level	90.3 dB(A)
Sound Power Level	101.3 dB(A)
Vibration Level	■
Dimensions (L x W x H)	455x245x200 mm
Net weight	4.8 - 4.9 kg (10.5 - 10.7 lbs.)
Power supply cord	0.3 m (0.98 ft)

\* Unless otherwise indicated, although 18V Li-Ion tools are portrayed with a battery, they are sold as tool only without battery and charger. This allows you to make up the most cost effective set of tools, batteries and chargers to suit your needs.



## DUC254Z Cordless Chain Saw

### Efficiency equivalent to 23mL class engine chain saw

**BL  
MOTOR**

#### High operating efficiency

Outer Rotor BL Motor provides high operating efficiency

+

#### High operability

Chain brake and Variable speed trigger switch provide high operability equivalent to engine chain saw.

+

#### Net weight

**3.1 kg**

with BL1850B ( 5.0Ah )  
Guide Bar 200mm, Saw Chain 90PX



#### Captive nuts

prevent loss of nut when removing sprocket cover to replace guide bar or saw chain.

#### Cutting work amount

Work volume on a single full battery charge

About

**160 cuts**



- 50mm cedar timber
- saw chain : 90PX
- Battery : BL1850B



### 18V LXT BL Brushless Cordless Chain Saw, Variable Speed, Brake, Soft Start



Guide Bar Length	250 mm
Chain Pitch / Chain Gauge	3/8" / 1.1 mm
	3/8" / 1.3 mm
Chain Speed	0 - 24 m/s (0 - 1,440 m/min)
Chain Oil Tank Volume	140 mL
Sound Pressure Level	92.2 dB(A)
Sound Power Level	103.2 dB(A)
Vibration Level	Cutting Wood: 3.1 m/s <sup>2</sup>
w/o Guide Bar :	w/o Guide Bar :
Dimensions (L x W x H)	258x184x191 mm
	w/ 25 cm (10") 90PX Sprocket Nose Bar:
	482x184x191 mm
Net Weight	2.8 - 3.2 kg

\* Unless otherwise indicated, although 18V Li-Ion tools are portrayed with a battery, they are sold as tool only without battery and charger. This allows you to make up the most cost effective set of tools, batteries and chargers to suit your needs.

## UC4051A

220V, 400mm, Automatic Oiling, Chain Brake, Brake, Torque Limiter, Soft Start, 2000W

## Electric Chain Saw



Provides better maneuverability.



Continuous rating input	2,000W
Chain speed per minute	870 m (2,900 ft)
Guide Bar Length	400 mm (16")
Saw chain	Pitch : 3/8"
	Gauge: 1.3 mm (0.050")
Sound Pressure Level	90.8 dB(A)
Sound Power Level	101.8 dB(A)
Vibration Level	5.2 m/s <sup>2</sup>
Dimensions (L x W x H)	505x200x220 mm
Net weight	5.6 kg (12.3 lbs.)
Power supply cord	0.3 m (0.98 ft)

## EA3502S

35cc, 400mm, Automatic Oiling, Chain Brake, Anti Vibration, Primer Pump, Capacitor Discharge Ignition

## Petrol Chain Saw



Premium hobby class chain saw for tough semi-professional use.



Saw chain	Pitch : 3/8"
	Gauge: 1.1 mm (0.043") / 1.3 mm (0.050")
Displacement	32 mL
Engine power	1.35 kW / 1.9 PS
Fuel Tank Capacity	0.4 L
Chain Oil Tank Volume	0.28 L
Sound Pressure Level	102.6 dB(A)
Sound Power Level	109.8 dB(A)
Vibration Level Front Grip	4.8 m/s <sup>2</sup>
Vibration Level Rear Grip	4.8 m/s <sup>2</sup>
Dimensions (L x W x H)	405x250x273 mm
Power head weight	4.0 kg (8.8 lbs.)

## EA4301F45C

42.4cc, 450mm, Automatic Oiling, Chain Brake, Anti Vibration, Primer Pump, Capacitor Discharge Ignition, Rapid Start

## Petrol Chain Saw



Farmer class chain saw for tough semi-professional use.



Saw chain	Pitch : 0.325" or 3/8"
	Gauge: 1.3 mm (0.050")
Displacement	42.4 mL
Engine power	2.2 kW / 3.0 PS
Fuel Tank Capacity	0.48 L
Chain Oil Tank Volume	0.28 L
Sound Pressure Level	100.8 dB(A)
Sound Power Level	110 dB(A)
Vibration Level Front Grip	3.6 m/s <sup>2</sup>
Vibration Level Rear Grip	3.2 m/s <sup>2</sup>
Dimensions (L x W x H)	416x248x279 mm
Power head weight	4.8 kg (10.5 lbs.)

## DUM604Z

18V LXT Li-Ion Cordless 16 cm (6-5/16") Grass Shear

## Cordless Grass Shear



Both trimmer blade and shear blade can be attached.

Grass receiver for reduced grass clean-ups.



Cutting Width	160 mm (6-5/16")
Depth Adjustment	15, 20, 25 mm (9/16", 13/16", 1")
Strokes Per Minute (SPM)	2,500
Continuous Use (min.)	w/ BL1860B / BL1840B / BL1830B / BL1815N: 250 / 160 / 125 / 60
Sound Pressure Level	76 dB(A)
Vibration Level	2.5 m/s <sup>2</sup> or less
Dimensions (L x W x H)	337x177x131 mm (13-1/4"x7"x5-1/8")
Net weight	1.4 - 1.8 kg (3.2 - 3.9 lbs.)

## DJR183Z

18V LXT Li-Ion Cordless 13mm Pruning / Recipro Saw, Var. Speed, Brake, Built-In Light

## Cordless Pruning / Recipro Saw



Toolless blade change system allows for faster blade installation and removal.



Capacity	Pipe : 50 mm (2") Wood: 50 mm (2")
Length of Stroke	13 mm (1/2")
Vibration Level	Cutting Boards: 8.0 m/s <sup>2</sup> Cutting Wooden Beams: 7.0 m/s <sup>2</sup>
Strokes Per Minute (SPM)	0-3,000
Sound Pressure Level	77 dB(A)
Dimensions (L x W x H)	392x81x209 mm
Net weight	1.5 - 1.7 kg (3.3 - 3.8 lbs.)

\* Unless otherwise indicated, although 18V Li-Ion tools are portrayed with a battery, they are sold as tool only without battery and charger. This allows you to make up the most cost effective set of tools, batteries and chargers to suit your needs.

**DUP362Z****Battery Powered Pruning Shears****18V X2 (36V) LXT Li-Ion Battery Powered Pruning Shears**

High cutting performance  
Smooth cutting similar to that of a hand pruner



**XPT**

Capacity	Max cutting : 33 mm (1-5/16")
Dimensions (L x W x H)	305x43x106 mm
Net weight	0.76 - 0.81 kg

**DUR181Z****Cordless String Trimmer****18V LXT Li-Ion Cordless String Trimmer**

Well balanced tool design.  
5-position pivoting head.



Cutting Width	Trimmer Head: 260 mm (10-1/4")
No Load Speed (RPM)	7,800
Sound Pressure Level	82 dB(A)
Sound Power Level	88.5 dB(A)
Vibration Level	2.5 m/s <sup>2</sup> or less
Dimensions (L x W x H)	1,229 - 1,433x267x186 - 257 mm
Max Run Time (min)	w/ BL1830B: 45
Net weight	2.8 - 3.1 kg (6.2 - 6.9 lbs.)

**DUR187LZ****Cordless Grass Trimmer****18V LXT BL ADT Cordless Grass Trimmer, Loop Handle, Brake, Reversing, Electronic 3-speed, Constant Speed, Soft Start**

BL motor located at trimmer head for improved balance and functionality with no loss of mechanical power.



Cutting Width	Nylon Cutting Head: 300 mm (11-3/4") Plastic Blade: 255 mm (10")
No Load Speed (RPM)	High / Med / Low / ADT Mode: 6,000 / 5,000 / 4,000 / 4,000 - 6,000
Spindle Size	M8 x 1.25 LH
Sound Pressure Level	Nylon Cutting Head: 74 dB(A)
Sound Power Level	Nylon Cutting Head: 84 dB(A)
Vibration Level	Front / Rear: 2.5 / 2.5 m/s <sup>2</sup> or less
Dimensions (L x W x H)	1,791x258x232 mm
Max Run Time (min)	Nylon Cutting Head, BL1860B: 168 Plastic Blade, BL1860B: 219
Net weight	3.4 - 3.7 kg (7.5 - 8.2 lbs.)

\*Standard with nylon cutting head.

**DUR364LZ****Cordless Grass Trimmer****18VX2(36V) LXT BL ADT Cordless Grass Trimmer, Loop Handle, Brake, Reversing, Electronic 2-speed, Constant Speed, Soft Start**

Powered by two 18V Li-Ion batteries in series.  
High power and more work amount.



Cutting Width	Trimmer Head: 350 mm (13-3/4") Plastic Blade: 255 mm (10")
No Load Speed (RPM)	High / Low: 6,500 / 5,000
Spindle Size	M8 x 1.25 RH
Sound Pressure Level	81 dB(A)
Sound Power Level	89 dB(A)
Vibration Level	Front / Rear: 2.5 / 2.5 m/s <sup>2</sup> or less
Dimensions (L x W x H)	1,754x310x229 mm (69"x12-1/4"x9")
Max Run Time (min)	w/ BL1850B: 100
Net weight	3.6 - 4.4 kg (8.0 - 9.7 lbs.)

\*Standard with nylon cutting head.

**DUR365UZ****Cordless Grass Trimmer****18VX2(36V) LXT BL ADT Cordless Grass Trimmer, Bike Handle, Brake, Reversing, Electronic 3-speed, Constant Speed, Soft Start**

Direct drive system featuring outer rotor brushless motor.  
Multifunctional control panel for operating main/variable speed control/reversing switches.



Cutting Width	Metal Blade: 230 mm (9") Trimmer Head: 350 mm (13-3/4") Plastic Blade: 255 mm (10")
No Load Speed (RPM)	High / Med / Low: 6,500 / 5,300 / 3,500
Spindle Size	M10 x 1.25 LH
Sound Pressure Level	Nylon Cutting Head: 77 dB(A)
Sound Power Level	Nylon Cutting Head: 90 dB(A)
Vibration Level	Left / Right: 2.5 / 2.5 m/s <sup>2</sup> or less
Dimensions (L x W x H)	1,754x610x460 mm (69"x24"x18-1/8")
Max Run Time (min)	w/ BL1850B: 490
Net weight	4.3 - 5.0 kg (9.6 - 11.0 lbs.)

\* Unless otherwise indicated, although 18V Li-Ion tools are portrayed with a battery, they are sold as tool only without battery and charger. This allows you to make up the most cost effective set of tools, batteries and chargers to suit your needs.



## 40.2mL, 40.2cc Petrol Brush Cutter

### Petrol Brush Cutter



Heavy duty and robust ideal for professional brush-cutting.



Displacement	40.2 mL
Engine power	1.40 kW / 2.0 PS
Fuel Tank Capacity	1.1 L
Spindle Size	M10 x 1.25LH
Dimensions (L x W x H)	1,710x670x430 mm
Net weight	7.3 kg (16.1 lbs.)

\*Standard with nylon cutting head.  
\*Blade not included.

## RBC413U

## 40.2mL, 40.2cc Petrol Brush Cutter

### Petrol Brush Cutter



Heavy duty and robust ideal for professional brush-cutting.



Displacement	40.2 mL
Engine power	1.40 kW / 2.0 PS
Fuel Tank Capacity	1.1 L
Spindle Size	M10 x 1.25LH
Sound Pressure Level	95.91 dB(A)
Sound Power Level	107.44 dB(A)
Vibration Level Left	4.39 m/s <sup>2</sup>
Handle	
Vibration Level Right	4.53 m/s <sup>2</sup>
Handle	
Dimensions (L x W x H)	1,710x650x435 mm
Net weight	7.1 kg (15.7 lbs.)

\*Standard with nylon cutting head.  
\*Blade not included.

## DLM380DZ

## 18V X2 (36V) LXT Li-Ion Cordless 38 cm (15") 2-in-1 Mower, Brake, Soft Start

### Cordless Lawn Mower



High maneuverability and environment-friendly.



Blade Type	2 Tooth, Rotary Type
Cutting Width	380 mm (15")
Cutting Height	25 - 75 mm (1" - 2-15/16")
No Load Speed (RPM)	3,700
Recommended mowing area	w/ BL1830B x2: 270 - 540 m <sup>2</sup>
Continuous Use (min.)	w/ BL1830B x2: 17
Sound Pressure Level	81 dB(A)
Sound Power Level	93 dB(A)
Vibration Level	2.5 m/s <sup>2</sup> or less
Dimensions (L x W x H)	1,145x465x1,023-1,070 mm
Net weight	14.5 kg (32.0 lbs.)

## DLM461Z

## 18V X2 (36V) LXT BL Brushless Cordless 46 cm (18") 3-in-1 Mower, Electronic 2-speed, Constant Speed, Soft Start

### Cordless Lawn Mower



The 460mm heavy duty steel deck & 4 swing back blades have been designed to withstand harsh conditions.



Blade Type	2 Tooth
Hole Diameter	10.0 mm (3/8")
Cutting Width	460 mm (18")
Cutting Height	20 - 75 mm (13/16" - 2-5/16")
No Load Speed (RPM)	2,500 - 3,300
Recommended mowing area	w/ BL1860B x2: 800 - 1,600 m <sup>2</sup> w/ BL1850B x2: 680 - 1,360 m <sup>2</sup> w/ BL1830B x2: 380 - 760 m <sup>2</sup> w/ BL1860B / BL1850B / BL1840B / BL1830B / BL1820B /
Continuous Use (min.)	BL1815N: 21 / 18 / 14 / 10 / 8 / 6
Sound Pressure Level	79 dB(A)
Sound Power Level	91 dB(A)
Vibration Level	2.5 m/s <sup>2</sup> or less
Dimensions (L x W x H)	During operation: 1,319-1,518x532x879-1,138 mm
Net weight	25.3 - 27.6 kg (55.8 - 60.8 lbs.)

## DUB183Z

## 18V LXT Li-Ion Cordless Variable 3-Speed Blower

### Cordless Blower



Long leaf blower nozzle with curved at end enables to use the machine comfortably in an upright standing posture.



Air volume	2.6 m <sup>3</sup> /min
Air speed	52 m/s
No Load Speed (RPM)	0-18,000
Sound Pressure Level	85 dB(A)
Sound Power Level	95 dB(A)
Vibration Level	2.5 m/s <sup>2</sup>
Dimensions (L x W x H)	845x155x212 mm
Net weight	1.7 - 2.0 kg (3.8 - 4.4 lbs.)

This machine cannot be used as a vacuum because it will get clogged with leaf or branch debris.

\* Unless otherwise indicated, although 18V Li-Ion tools are portrayed with a battery, they are sold as tool only without battery and charger. This allows you to make up the most cost effective set of tools, batteries and chargers to suit your needs.



**DUB361Z****18V X2 (36V) LXT Li-Ion Cordless 2-Speed Blower****Cordless Blower**

Cordless blower powered by two 18V Li-Ion batteries in series.



Max Air Volume	High: 4.4 m <sup>3</sup> /min (155 CFM) Low: 2.6 m <sup>3</sup> /min (92 CFM)
Max Air Velocity	High: 93 m/s (208 MPH) Low: 57 m/s (128 MPH)
No Load Speed (RPM)	High: 17,000 Low: 10,000
Sound Pressure Level	82.3 dB(A)
Sound Power Level	94.7 dB(A)
Vibration Level	2.5 m/s <sup>2</sup> or less
Dimensions (L x W x H)	905x141x194 mm
Net weight	3.1 - 3.2 kg (6.8 - 7.1 lbs.)

**DUB362Z****18V X2 (36V) LXT BL Brushless Cordless Variable Blower****Cordless Blower**

High air volume and air speed delivered by brushless motor and two 18V Li-Ion batteries in series.



Max Air Volume	13.4 m <sup>3</sup> /min (473 CFM)
Max Air Velocity	54 m/s (120 MPH)
No Load Speed (RPM)	11,400 - 21,500
Sound Pressure Level	79.1 dB(A)
Sound Power Level	93.5 dB(A)
Vibration Level	2.5 m/s <sup>2</sup> or less
Dimensions	830/880/930x205x295 mm
Net weight	3.5 - 4.2 kg (7.7 - 9.3 lbs.)

**DUH523Z****18V LXT Li-Ion Cordless Hedge Trimmer, Brake****Cordless Hedge Trimmer**

Rubberized soft grip provides comfortable and sure grip.

User-replaced blade.



Blade Length	520 mm (20-1/2")
Strokes Per Minute (SPM)	2,700
Tooth Spacing	26 mm (1")
Sound Pressure Level	77 dB(A)
Sound Power Level	84.3 dB(A)
Vibration Level	2.5 m/s <sup>2</sup>
Dimensions (L x W x H)	938x195x193 mm
Net weight	3.0 - 3.4 kg

**DUH651Z****18V X2 (36V) LXT Li-Ion Cordless Hedge Trimmer, Variable Speed, Brake, Soft Start****Cordless Hedge Trimmer**

Two 18V LXT Li-Ion batteries deliver the power and performance for corded demands without leaving the 18V LXT platform. High maneuverability and environment-friendly. Rotatable rear handle.



Blade Length	650 mm (25-1/2")
Strokes Per Minute (SPM)	2,000 - 3,600
Tooth Spacing	36 mm (1-7/16")
Sound Pressure Level	82 dB(A)
Sound Power Level	91.1 dB(A)
Vibration Level	2.5 m/s <sup>2</sup> or less
Dimensions (L x W x H)	1,135x225x200 mm
Net weight	4.7 - 5.5 kg

**UH6570****220V Hedge Trimmer, Brake****Hedge Trimmer**

More improved handling with ergonomic multi-grip system.



Continuous rating input	550W
Blade Length	650 mm (25-1/2")
Strokes Per Minute (SPM)	3,200
Tooth Spacing	18 mm (11/16")
Sound Pressure Level	89.9 dB(A)
Sound Power Level	97.9 dB(A)
Vibration Level	6.7 m/s <sup>2</sup>
Dimensions (L x W x H)	1,042x223x206 mm
Net weight	3.8 - 3.9 kg (8.4 - 8.5 lbs.)
Power supply cord	0.3 m (0.98 ft)

\* Unless otherwise indicated, although 18V Li-Ion tools are portrayed with a battery, they are sold as tool only without battery and charger. This allows you to make up the most cost effective set of tools, batteries and chargers to suit your needs.

## DUH602Z

### Cordless Hedge Trimmer

## 18V LXT BL Brushless Cordless Hedge Trimmer

#### Light weight

**3.8kg**

with BL1850B ( 5.0Ah )  
battery

#### High speed

strokes per minute

**4,400min<sup>-1</sup>**

High speed mode  
(No load speed)

#### Variable 3-speed



- High : 0-4,400 SPM
- Medium : 0-3,600 SPM
- Low : 0-2,000 SPM

**BL  
MOTOR**

**High Power and  
High Speed**




### DUH501 / DUH601 / DUH751


#### Optimum blade shape for smooth cutting



Sharp edge blades :  
Upper blade...curving downward  
Lower blade...curving upward



Twigs are caught easily and held firmly



#### Standard blade


#### Standard blade





#### Anti-vibration structure

consisting of Motor-crank section and handle section  
linked by 5 cushions to absorb vibration from blade  
and motor-crank section



#### Anti-vibration structure



#### Predecessor model



#### Reverse rotation system



#### Adjustable rear handle

- Locks at 45° and 90° left and right and 0°.
- Makes vertical and angled trimming easier and faster.



### 18V LXT BL Brushless Cordless Hedge Trimmer



**BL  
MOTOR**



Blade Length	600 mm (23-5/8")
Max Cutting Capacity	
Strokes Per Minute (SPM)	High / Med / Low: 0 - 4,400 / 0 - 3,600 / 0 - 2,000
Max Output	520W
Dimensions (L x W x H)	1,121x192x225 mm (44-1/8"x7-1/2"x8-7/8")
Net weight	3.9 - 4.3 kg (8.5 - 9.4 lbs.)

\* Unless otherwise indicated, although 18V Li-Ion tools are portrayed with a battery, they are sold as tool only without battery and charger. This allows you to make up the most cost effective set of tools, batteries and chargers to suit your needs.



**DCU180Z**

Cordless Wheelbarrow

**18V LXT BL Brushless Battery Powered Wheelbarrow, 130 Kg (290 Lbs.) Capacity**

all kinds of heavy loads with optional heavy duty and bucket.

**BL MOTOR XPT**

Max Run Time (min)	w/ BL1860B x2: 120
Max Load Capacity	130 kg (290 lbs.)
Traveling Speed	Forward, High / Low: 0 - 3.5 / 0 - 1.5 km/h
	Reverse: 0 - 1 km/h
Max Climbing Capacity	12°
Dimensions (L x W x H)	When carrier is installed / During operation: 1,315x1,060x900 mm
Net weight	39.3 - 44.8 kg (86.5 - 98.7 lbs.)

**Lighter****Long Life****Smaller****More Work****Stronger****Smarter****BL  
MOTOR**

\* Unless otherwise indicated, although 18V Li-Ion tools are portrayed with a battery, they are sold as tool only without battery and charger. This allows you to make up the most cost effective set of tools, batteries and chargers to suit your needs.



**36V**  
**18V + 18V**

**18V Intelligent Charger and Batteries fit all 18V Tools**  
Excludes HP347 & HP457 white/black battery models  
\*Charge time from cold - Charges all batteries

**6.0Ah BATTERY**  
BL1860B  
Charge time: **55 min!**

**1.5Ah BATTERY**  
BL1815N  
Charge time: **15 min!**

**3.0Ah BATTERY**  
BL1830B  
Charge time: **22 min!**

**5.0Ah BATTERY**  
BL1850B  
Charge time: **45 min!**

**ADAPTOR FOR USB**  
ADP05

**LED FLASHLIGHT**  
DML800  
DML801  
DML802  
DML807

**LED WORKLIGHT**  
DNL805

**AUTOMATIC SWING FAN**  
DCF102Z

**PLANER**  
DKP180Z

**RANDOM ORBIT SANDER**  
DGO180Z

**MULTI TOOL**  
DTM50Z

**AUTO FEED SCREWDRIVER**  
DPS59ZJ

**SCREWDRIVER**  
DFS250ZJ  
DFS252ZJ  
DFS343ZJ  
DFS343ZJ

**IMPACT WRENCH**  
DTW190ZK  
DTW251ZK  
DTW285ZK  
DTW450ZK  
DTW1001ZJ  
DTW1002ZJ

**DRIVER DRILLS**  
DDF083Z  
DDF483ZJ  
DDF481ZJ  
DDF484ZJ

**IMPACT DRIVER DRILL**  
DHP453ZK  
DHP458ZK  
DHP485Z  
DHP481ZK  
DHP483ZJ  
DHP482ZJ

**IMPACT DRIVER**  
DTD129ZK  
DTD152Z  
DTD153ZJ  
DTD154Z  
DTD155ZJ  
DTD170ZJ

**OIL-PULSE DRIVER**  
DPS147ZJ

**ROTARY HAMMER**  
DHR135ZK  
DHR202ZK  
DHR242ZJ

**RECIPRO SAW**  
DJR183Z  
DJR185ZK  
DJR187ZK

**JIG SAW**  
DJV180ZK  
DJV181ZJ  
DJV182ZK

**TWO PORT MULTI FAST CHARGER**  
DC18RD

**FAST CHARGER**  
DC18RC

**VACUUM CLEANER**  
DVC360Z  
DVC260Z

**BACKPACK VACUUM CLEANER**  
DVC260Z

**VACUUM CLEANER**  
DVC360Z  
DVC862ZL

**BLOWER**  
DUB381Z  
DUB382Z

**GRASS TRIMMER**  
DUR384ZLZ  
DUR3650Z

**HEDGE TRIMMER**  
DUH651Z

**CHAIN SAW**  
DUC392Z  
DUC400Z

**SLIDE COMPOUND MITRE SAW**  
DLS714Z

**ANGLE GRINDER**  
DGA900ZK

**ROTARY HAMMER**  
DHR203ZK  
DHR400

**RECIPRO SAW**  
DUR360ZK

**CIRCULAR SAW**  
DHS710Z

**PLUNGE CUT SAW**  
DSP600J

**CUT OFF SAW**  
DLW140Z

**BLOWER**  
DUB183Z  
DUB185Z

**TRIMMER**  
DRT502J  
DRT502JX2

**BISCUIT JOINER**  
DPJ180ZJ

**METAL CUTTER**  
DCS551Z

**CIRCULAR SAW**  
DHS680ZJ  
DHS610ZK

**CONCRETE VIBRATOR**  
DVR450Z

**HEDGE TRIMMER**  
DUR623Z

**GRASS TRIMMER**  
DUR187Z

**GRASS SHEAR**  
DUM604Z

**CHAIN SAW**  
DUC122Z

**CLEANER**  
DLC180Z

**ROBOTIC CLEANER**  
DRC200Z

**DUST EXTRACTOR**  
DVC350Z

**CAUL KING GUN**  
DCG180ZK

**CUT-OUT TOOL**  
DCO180Z

**DIE GRINDER**  
DGD800Z  
DGD801ZK

**ANGLE GRINDER**  
DGA452ZK  
DGA453ZK  
DGA458ZJ

**STRAIGHT SHEAR**  
DSS161ZJ

**NIBBLER**  
DIN161Z

**ANGLE DRILL**  
DDA350ZK

**ANGLE IMPACT DRIVER**  
DIL081ZJ

**IMPACT WRENCH**  
DIL083ZJ

**PIN NAILER**  
DPT351Z  
DPT353ZJ

**STAPLER**  
DS1271Z

**PORTABLE BAND SAW**  
DPB180ZK

**DRY WALL SAW**  
DSD180ZJ

**WHEEL BARROW**  
DCU180Z

**HEATED JACKET**  
DCJ200

**OPTIONAL ACCESSORIES**

All our 18V models use the same battery platform.

There is limited stock availability on models denoted in red